



G4 : Fiber cassette filter for coarse dust particles filtration
F7 : Compact type filter for fine dust particles filtration
Heat Recovery : Heat recovery with run-around coils
Heating/Cooling Coil : Optionally, hydronic coil or DX coil product can be selected.
Fan : Plug-type fan with backward curved blades

ESP-E : 96% (@3µm) Efficiency electrostatic filter Ashrae Test
OPTIONS : [ESP-F : 99% Efficiency electrostatic filter ISO16890] / [MPF 8 : ISO ePM1 65% ISO16890]
Heat Recovery : Heat recovery with run-around coils
OPTIONS : [UVC-P : Optionally, ultraviolet lamps that produce very intense ozone] / [Boş Empty]
Activated Carbon : 400mm cylindrical cartridges made of high efficiency 4mm pellet carbon coals
Fan : Plug-type fan with backward curved blades
Control Board : Fan speed control, filter dirty status, unit on/off operations, make-up unit control are performed with the 7" touch panel supplied as standard



Model	Dimensions (mm)								Weight (kg)			
	W	L	H	HF	W1xH1	W2xH2	W3xH3	W4xH4	G1	G2	G3	G4
REC 50	1300	4400	1600	800	1200x700	1200x300	1200x500	1200x300	280	350	210	140
REC 100	1300	4400	3000	1500	1400x1400	1400x400	1400x800	1400x500	510	605	370	255
REC 150	1900	4400	3000	1500	1800x1400	1800x500	1800x800	1800x600	780	980	575	390